

16-Port Full Gigabit Managed Ethernet Switch

(IS700-16E)

Product Description

The IS700-16E is a full gigabit L2+ managed industrial Ethernet switch. It has 16*10/100/1000Base-T RJ45 ports. Each port can support wire-speed forwarding.

The IS700-16E has L2+ network management function, support IPV4/IPV6 management, static route full line-rate forwarding, security protection mechanism, ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Support multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS(<20ms) to improve link backup and network reliability. When the one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as port traffic control, VLAN division, and SNMP through the Web network management mode. Industrial switches meet the needs of the industrial Ethernet application environment. It is suitable for intelligent transportation, rail transit, power industry, mining, petroleum, shipping, metallurgy, and green energy construction and other industrial scenarios to form a cost-effective, stable, and reliable network.



Product Features

● Full Gigabit access, wire-speed transmission

- ✧ Support line-speed full Gigabit Ethernet port, which facilitates flexible networking of users and meets networking requirements in various scenarios.
- ✧ Support non-blocking wire-speed forwarding.
- ✧ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

● Security

- ✧ 802.1X authentication.
- ✧ Port isolation, Storm control.
- ✧ IP-MAC-VLAN-Port binding.

● Strong business processing capability

- ✧ ERPS/STP/RSTP/MSTP.
- ✧ Static and dynamic aggregation.
- ✧ IGMP V1/V2 and IGMP Snooping.
- ✧ IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN, and QinQ configuration.
- ✧ QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including EQU, SP, WRR & SP+WRR.
- ✧ ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.

● Stable and reliable

- ✧ CCC, CE, FCC, RoHS.
- ✧ Low power consumption, no fan, aluminum shell.
- ✧ The user-friendly panel, it can show the device status through the LED indicator of PWR, SYS, Link, L/A.
- ✧ The DIN rail industrial switch series products do not have a power supply by default and need to be purchased.

● Easy operation and maintenance management

- ✧ HTTPS, SSLV3, and SSHV1/V2.
- ✧ RMON, system log, LLDP, and port traffic statistics.
- ✧ CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- ✧ Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

Product Parameters


Model	IS700-16E		
Interface Characteristics			
Fixed Port			16*10/100/1000Base-T RJ45 ports (Data)
			1*RS232 Console port (115200,N,8,1)
			Power-off alarm switch (FAULT)
			2 set of V+, V- redundant DC power interface (6 Pin Phoenix terminal)
Ethernet Port			Port 1-16 support 10/100/1000Base-T,auto-sensing,Full/half duplex MDI/MDI-X self-adaption
Twisted Transmission	Pair		10BASE-T: Cat3,4,5 UTP(≤100 meter)
			100BASE-TX: Cat5 or later UTP(≤100 meter)
			1000BASE-T: Cat5e or later UTP(≤100 meter)
Chip Parameter			
Network Management Type			L2+
Network Protocol			IEEE802.3 10BASE-T, IEEE802.3i 10Base-T
			IEEE802.3u 100Base-TX , IEEE802.3ab 1000Base-T
			IEEE802.3x
Forwarding Mode			Store and Forward(Full Wire Speed)
Switching Capacity			256Gbps (Non-blocking)
Forwarding			23.81Mpps
Rate@64byte			
MAC			8K
Buffer Memory			6M
Jumbo Frame			9.6K
LED Indicator			Power: PWR(green), system: SYS(green), Network: Link (yellow)
Reset Switch			Yes. press and hold for 10 seconds and then release to restore factory settings
Power			
Total PWR / Input Voltage			24W/(DC12-48V)
Power Consumption			Standby<10W, Full Load<20W

Power Interface	Input	12-48VDC, 6 Pin industrial Phoenix terminal, support anti-reverse protection.
Power Supply		No, optional 24V/24W industrial power supply
Physical Parameter		
Operation TEMP / Humidity		-40~+80°C;5%~90% RH Non condensing
Storage TEMP / Humidity		-40~+85°C;5%~95% RH Non condensing
Dimension (L*W*H)		165*148*54mm
Net /Gross Weight		<1.2kg / <1.5kg
Installation		Desktop, DIN rail
Certification & Warranty		
Lightning protection protection level	/	Port lightning protection: 6kV 8/20us; Protection level: IP40
		IEC61000-4-2(ESD):±8kV contact discharge,±15kV air discharge
		IEC61000-4-3(RS):10V/m(80~1000MHz)
		IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV
		IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable:±4kV
		IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz)
		IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s
		IEC61000-4-9(pulsed magnet field):1000A/m
		IEC61000-4-10(damped oscillation):30A/m 1MHz
		IEC61000-4-12/18(shockwave):CM 2.5kV,DM 1kV
		IEC61000-4-16(common-mode transmission):30V; 300V,1s
		FCC Part 15/CISPR22(EN55022):Class A
		IEC61000-6-2(Common Industrial Standard)
Mechanical Properties		IEC60068-2-6 (anti vibration)
		IEC60068-2-27 (anti shock)
		IEC60068-2-32 (free fall)
Certification		CCC;CE mark, commercial; CE/LVD EN60950;FCC Part 15 Class B; RoHS
Warranty		5 years, lifelong maintenance.
Network Management Features		


Interface	IEEE802.3X (Full-duplex)
	Port temperature protection setting
	Port green Ethernet Energy-saving setting
	Broadcast storm control based on port speed
	The speed limit of the message flow in the access port.
	The minimum particle size is 64Kbps.
Layer 3 Features	L2+ network management ,IPV4/IPV6 management
	L3 soft routing forwarding,
	Static route, Default route @ 128 pcs, APR @ 1024 pcs
VLAN	4K VLAN based on port, IEEE802.1q
	VLAN based on the protocol
	VLAN based on MAC
	Voice VLAN, QinQ configuration
	Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation
	Max 8 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s)
Industrial Ring Network Protocol	G.8032 (ERPS),Recovery time less than 20ms
	250 Ring at most, Max 250 devices per ring.
Multicast	MLD Snooping v1/v2,Multicast VLAN
	IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting
	Flow-based Packet Filtering
	8*Output queues of each port
	802.1p/DSCP priority mapping
	Diff-Serv QoS,Priority Mark/Remark
	Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL,ACL based on port and VLAN
	L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.

Security	IP-MAC-VLAN-Port binding
	ARP inspection,Anti-DoS attack
	AAA & RADIUS,MAC learning limit
	Mac black holes,IP source protection
	IEEE802.1X & MAC address authentication
	Broadcast storm control,Backup for host datum
	SSH 2.0,SSL,Port isolation,ARP message speed limit
	User hierarchical management and password protection
DHCP	DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay
Management	One-key recovery
	Cable Diagnose,LLDP
	Web Management (HTTPS)
	NTP,System work log,Ping Test
	CPU instant utilization status view
	Console/AUX Modem/Telnet/SSH2.0 CLI
	Download & Management on FTP, TFTP, Xmodem, SFTP,SNMP V1/V2C/V3
	NMS - smart network management system platform(LLDP+SNMP)
System	Category 5 Ethernet network cable
	Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later;
	TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network

Product size



Application



Order Information

Model	Description	Recommended Power Supply
IS700-16E	L2+ managed industrial Ethernet switch with 16* 10/100/1000M RJ45 ports. It can support DC dual power supply input and DIN rail mounting.	24W

Note: The DIN rail industrial switch series products are not equipped with power supply by default and need to be purchased. Please refer to the accessory product information.

Packing List

	CONTENT	QTY	UNIT
PACKING LIST	16-port full gigabit managed industrial Ethernet switch	1	SET
	RJ45-DB9 Line	1	PC
	User Guide	1	PC
	Warranty Card	1	PC