

24-Port Full Gigabit Managed Industrial Ethernet Switch

(IS700-16E8F)

Product Description

The IS700-16E8F is a full gigabit L2+ managed industrial Ethernet fiber switch. It has 16*10/100/1000Base-T RJ45 ports and 8*100/1000Base-X SFP fiber slot ports. Each port can support wire-speed forwarding.

The IS700-16E8F has L2+ network management function, support IPV4/IPV6 management, static route full line-rate forwarding, security protection mechanism, ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Support multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS(<20ms) to improve link backup and network reliability. When the one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as port traffic control, VLAN division, and SNMP through the Web network management mode. Industrial switches meet the needs of the industrial Ethernet application environment. It is suitable for intelligent transportation, rail transit, power industry, mining, petroleum, shipping, metallurgy, and green energy construction and other industrial scenarios to form a cost-effective, stable, and reliable network.



Product Features

● Gigabit access , SFP port uplink

- ✧ All series supports Ethernet port and SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ✧ Support non-blocking wire-speed forwarding.
- ✧ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

● Security

- ✧ 802.1X authentication.
- ✧ Port isolation, Storm control.
- ✧ IP-MAC-VLAN-Port binding.

● Strong business processing capability

- ✧ ERPS/STP/RSTP/MSTP.
- ✧ Static and dynamic aggregation.
- ✧ IGMP V1/V2 and IGMP Snooping.
- ✧ IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN, and QinQ configuration.
- ✧ QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including EQU, SP, WRR & SP+WRR.
- ✧ ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.

● Stable and reliable

- ✧ CCC, CE, FCC, RoHS.
- ✧ Low power consumption, no fan, aluminum shell.
- ✧ The user-friendly panel, it can show the device status through the LED indicator of PWR, SYS, Link, L/A.
- ✧ The DIN rail industrial switch series products do not have a power supply by default and need to be purchased.

● Easy operation and maintenance management

- ✧ HTTPS, SSLV3, and SSHV1/V2.
- ✧ RMON, system log, LLDP, and port traffic statistics.
- ✧ CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- ✧ Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

Product Parameters

Model

IS700-16E8F

Interface Characteristics

		16*10/100/1000Base-T RJ45 ports (Data)
		8*100/1000Base-X uplink SFP slot ports (Data)
Fixed Port		1 * RS232 console port(115200,N,8,1)
		Power-off alarm switch (FAULT)
		2 set of V+, V- redundant DC power interface (6 Pin Phoenix terminal)
Ethernet Port		Port 1-16 support 10/100/1000Base-T,auto-sensing,Full/half duplex MDI/MDI-X self-adaption
Twisted Transmission	Pair	10BASE-T: Cat3,4,5 UTP(≤ 100 meter) 100BASE-TX: Cat5 or later UTP(≤ 100 meter) 1000BASE-T: Cat5e or later UTP(≤ 100 meter)
Optical Fiber Port		Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
SFP Port Expansion		Turbo overclocking 2.5G optical module and ring
Optical Distance	Cable/	Multi mode: 850nm / 0 ~ 500M, single mode: 1310nm / 0 ~ 40KM, 1550nm / 0 ~ 120KM.

Chip Parameter

Network Management Type	L2+
	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T
Network Protocol	IEEE802.3u 100Base-TX , IEEE802.3ab 1000Base-T
	IEEE802.3z 1000Base-X
	IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	256Gbps
Forwarding Rate@64byte	35.71Mpps
MAC	8K
Buffer Memory	8M

Jumbo Frame	9.6K
LED Indicator	Power: PWR (green), System: SYS (green), Network: Link (yellow), Fiber Port : L/A (green)
Reset Switch	Yes. press and hold for 10 seconds and then release to restore factory settings

Power

Total PWR / Input Voltage	30W/(DC12-48V)
Power Consumption	Standby<10W, Full Load<30W
Working Voltage	12-48VDC, 6 Pin industrial Phoenix terminal, support anti-reverse protection.
Power Supply	No, optional 24V/30W industrial power supply

Physical Parameter

Operation TEMP / Humidity	-40~+80°C;5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+85°C;5%~95% RH Non condensing
Dimension (L*W*H)	166*149*89mm
Net /Gross Weight	<2.2kg / <2.8kg
Installation	Desktop, DIN rail

Certification & Warranty

Lightning protection level	/	Port lightning protection: 6KV 8/20us; Protection level: IP40
		IEC61000-4-2(ESD):±8kV contact discharge,±15kV air discharge
		IEC61000-4-3(RS):10V/m(80~1000MHz)
		IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV
		IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable:±4kV
		IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz)
		IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s
		IEC61000-4-9(pulsed magnet field):1000A/m
		IEC61000-4-10(damped oscillation):30A/m 1MHz
		IEC61000-4-12/18(shockwave):CM 2.5kV,DM 1kV
Mechanical		IEC61000-4-16(common-mode transmission):30V; 300V,1s
		FCC Part 15/CISPR22(EN55022):Class A
		IEC61000-6-2(Common Industrial Standard)
		IEC60068-2-6 (anti vibration)


Properties	IEC60068-2-27 (anti shock) IEC60068-2-32 (free fall)
Certification	CCC;CE mark, commercial; CE/LVD EN60950;FCC Part 15 Class B; RoHS
Warranty	5 years, lifelong maintenance.

Network Management Features

	IEEE802.3X (Full-duplex)
	Port temperature protection setting
	Port green Ethernet Energy-saving setting
Interface	Broadcast storm control based on port speed The speed limit of the message flow in the access port. The minimum particle size is 64Kbps.
	L2+ network management ,IPV4/IPV6 management
Layer 3 Features	L3 soft routing forwarding, Static route, Default route @ 128 pcs, APR @ 1024 pcs 4K VLAN based on port, IEEE802.1q VLAN based on the protocol
VLAN	VLAN based on MAC Voice VLAN, QinQ configuration Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation Max 12 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s)
Industrial Ring Network Protocol	G.8032 (ERPS),Recovery time less than 20ms 255 Ring at most, Max 1024 devices per ring.
Multicast	MLD Snooping v1/v2,Multicast VLAN IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port Flow-based Rate Limiting
QoS	Flow-based Packet Filtering 8*Output queues of each port 802.1p/DSCP priority mapping

	Diff-Serv QoS,Priority Mark/Remark
	Queue Scheduling Algorithm (SP, WRR, SP+WRR)
	Port-based Issuing ACL,ACL based on port and VLAN
ACL	L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
	IP-MAC-VLAN-Port binding
	ARP inspection,Anti-DoS attack
	AAA & RADIUS,MAC learning limit
Security	Mac black holes,IP source protection
	IEEE802.1X & MAC address authentication
	Broadcast storm control,Backup for host datum
	SSH 2.0,SSL,Port isolation,ARP message speed limit
	User hierarchical management and password protection
DHCP	DHCP Client,DHCP Snooping, DHCP Server,DHCP Relay
	One-key recovery
	Cable Diagnose,LLDP
	Web Management (HTTPS)
Management	NTP,System work log,Ping Test
	CPU instant utilization status view
	Console/AUX Modem/Telnet/SSH2.0 CLI
	Download & Management on FTP, TFTP, Xmodem, SFTP,SNMP V1/V2C/V3
	NMS - smart network management system platform(LLDP+SNMP)
	Category 5 Ethernet network cable
System	Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later;
	TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network

Product size



Application

